



## CLIMATISEURS SPLIT SYSTEM GAINABLE BLUE ICE SERIE "CR" GAZ R410A

SPECIFICATIONS TECHNIQUES	MODELES	CR35	CR40	CR45	CR50	CR65
Puissance frigorifique nominale	Kw	8.79	10.25	12.31	14.06	16.41
	BTU/h	30000	35000	42000	48000	56000
	Kcal/h	7500	8750	10500	12000	14000
Puissance calorifique nominale	Kw	8.79	10.25	12.31	14.06	16.41
	BTU/h	30000	35000	42000	48000	56000
	Kcal/h	7500	8750	10500	12000	14000
Tension d'alimentation	1PH 50HZ	230	230	230	-	-
Tension d'alimentation	3PH 50HZ	-	400	400	400	400
Intensité nominale en froid	Amp.	13	14.7	18.2	7.8	8.5
Intensité nominale en chaud	Amp.	13	14.7	18.2	7.8	8.5
Consommation en Froid	Kw	2.8	3.2	4	4.5	5.3
Consommation en Chaud	Kw	2.8	3.2	4	4.5	5.3
Débit d'air unité intérieure	M3/h	1700	1870	2210	2550	3060
Protection électrique 1PH	Amp.	25	30	30	-	-
Protection électrique 3PH	Amp.	3x8	3x10	3x10	3x16	3x16
Charge initiale	Kg	2.5	2.8	3.0	3.2	4.2
Déshumidification	L/h	3.5	4.8	4	4.5	4.8
C.O.P. (frig.)	W/W	3.14	3.2	3.1	3.12	3.12
C.O.P. (cal.)	W/W	3.14	3.2	3.1	3.12	3.12
Dimensions (cm) Unité intérieure	H/L/P	40/70/58	40/90/58	40/90/58	40/112/58	40/112/58
Dimensions (cm) Unité extérieure	H/L/P	73/86/37	95/98/41	95/98/41	124/95/42	124/95/42
Poids unite intérieure	Kg	40	40	45	55	60
Poids unite extérieure	Kg	65	80	85	90	100
Diamètre: tube "fluide"	Inch	5/8	5/8	5/8	3/4	3/4
Diamètre: tube "gaz"	Inch	3/8	3/8	3/8	1/2	1/2
Niveau sonore unité int.	Db(A)*	38/40/42	41/43/45	42/44/46	45/47/50	45/49/52
Niveau sonore unité ext.	Db(A)*	50	50	53	55	58

